


DFAS / MFE

SOLID CARBIDE FLAT BOTTOM DRILLS FOR
HIGH EFFICIENCY DRILLING OF VARIOUS APPLICATIONS



DFAS / DFAS-E

SOLID CARBIDE FLAT BOTTOM DRILLS WITH INTERNAL COOLANT DC 3.0 – 14



OPTIMISED CHIP CONTROL AND LOAD REDUCTION

The thinned centre cutting edge generates low cutting resistance and thereby creates an optimum chip geometry for a smoother chip flow.

TRI-COOLING TECHNOLOGY FOR ALL DIAMETERS

Coolant flow is increased without reducing the rigidity of the drill. The extra coolant flow dramatically improves chip evacuation and dissipates cutting heat. This enables stable machining of stainless steel and titanium alloys.

ORIGINAL SHARP CUTTING EDGE SHAPE

Strength is ensured by providing a flat land (gash) at the corner and by adopting a sharp main cutting edge, burrs are suppressed.



COMPARISON OF BURRS WHEN MACHINING TITANIUM ALLOY



DFAS
0.08 mm



Conventional
0.12 mm

COATED GRADE DP102A

DP102A coated grade provides excellent lubricity and long-term durability, achieving excellent wear resistance at low to medium cutting speeds.

MINI-MFE

SMALL DIAMETER SOLID CARBIDE FLAT BOTTOM DRILLS DC 0.75 – 2.95



UNIQUE SHARP CUTTING EDGES


The flat lands on the corners provide greater strength and sharpness for substantial reduction of burrs.

EXCELLENT CHIP CONTROL

End geometry that combines different radii forms a strong cutting edge and provides excellent chip control.

POINT THINNING FOR LOWER THRUST FORCE

The mutli radius point geometry in combination with the thinned point forms ideal chip shapes, thereby dramatically reducing cutting resistance.



MFE



Conventional

COATED GRADE DP102A

DP102A is a PVD coated cemented carbide grade specialised for drills. The coating has high adhesion and stability even on a sharp cutting edge. This greatly improves wear resistance and is ideal for drilling small diameter holes at low speed and feed conditions.

SHARP CUTTING EDGES WITH LONG TOOL LIFE

Material	X5CrNi189
Tool/ Drill	MFE0100X02S030
L/D (mm)	2
Vc (m/min)	25
fr (mm/rev.)	0.007
Machine	Vertical MC (BT40)

100 HOLES



MFE




Conventional

500 HOLES



MFE




Conventional



Al-Cr-N Based PVD Coating


MFE

SOLID CARBIDE FLAT BOTTOM DRILLS DC 3.0 – 20.0



EXCELLENT CHIP CONTROL

The combination of different radius geometries provides a strong cutting edge and excellent chip control.



Material	DIN CK 50
Vc (m/min)	50
fr (mm/rev.)	0.07

NEW "Z" POINT THINNING WITH LOWER THRUST FORCE

New point thinning provides excellent chip evacuation.

GASH LAND FOR A STRONGER CORNER


Gash land (0 degree rake) provides excellent chipping resistance.

ZERO-μ SURFACE


Smooth surface provides reduced deflection and excellent positional accuracy.

COATED GRADE DP1020

DP1020 grade offers excellent wear resistance and reduced friction for longer tool life and covers a wide range of applications.







With accumulated AlTiCrN based PVD coating






DFAS / MFE

HIGH EFFICIENCY OVER A WIDE APPLICATION RANGE

HIGH EFFICIENCY COUNTER BORING IN VARIOUS TYPES OF MACHINING WITH EXCELLENT CHIPPING RESISTANCE

Spot Facing and Pilot Drilling				
	Angled surface	Offset circular surface	Shoulder	Deep hole
				
NEW MFE	⊙	⊙	⊙	
DFAS 3D	⊙	⊙	⊙	
NEW DFAS 5D				⊙


LOW CUTTING FORCES REDUCES BURRS DUE TO ITS UNIQUE SHAPE, IT IS POSSIBLE TO CORRECT ECCENTRIC HOLES AND CAST HOLES WITH HIGH ACCURACY

	Drilling		Reform	
	Thin plate	Intersecting hole	Eccentric and cast holes	
				
NEW MFE	⊙	⊙	⊙	
DFAS 3D	⊙	⊙	⊙	
NEW DFAS 5D				

DFAS-E



SOLID CARBIDE FLAT BOTTOM DRILLS m7 TOLERANCE



	$3 < DC \leq 6$	$6 < DC \leq 10$	$10 < DC \leq 14$
	+ 0.016	+ 0.021	+ 0.025
	+ 0.004	+ 0.006	+ 0.007
	$4 < DCONMS \leq 6$	$6 < DCONMS \leq 10$	$10 < DCONMS \leq 14$
	0	0	0
	- 0.008	- 0.009	- 0.011

Order number	DP102A	DC	L/D	LU	LCF	LS	OAL*	DCONMS	Type
DFAS0300X03S060E	●	3	3	9	14	40.4	62	6	2
DFAS0310X03S060E	●	3.1	3	9.3	16	38.6	62	6	2
DFAS0320X03S060E	●	3.2	3	9.6	16	38.8	62	6	2
DFAS0330X03S060E	●	3.3	3	9.9	16	39.0	62	6	2
DFAS0340X03S060E	●	3.4	3	10.2	16	39.1	62	6	2
DFAS0350X03S060E	●	3.5	3	10.5	16	39.3	62	6	2
DFAS0360X03S060E	●	3.6	3	10.8	17	38.5	62	6	2
DFAS0370X03S060E	●	3.7	3	11.1	17	38.7	62	6	2
DFAS0380X03S060E	●	3.8	3	11.4	18	41.9	66	6	2
DFAS0390X03S060E	●	3.9	3	11.7	18	42.1	66	6	2
DFAS0400X03S060E	●	4	3	12	18	42.3	66	6	2
DFAS0410X03S060E	●	4.1	3	12.3	20	40.5	66	6	2
DFAS0420X03S060E	●	4.2	3	12.6	20	40.6	66	6	2
DFAS0430X03S060E	●	4.3	3	12.9	20	40.8	66	6	2
DFAS0440X03S060E	●	4.4	3	13.2	20	41.0	66	6	2
DFAS0450X03S060E	●	4.5	3	13.5	20	41.2	66	6	2
DFAS0460X03S060E	●	4.6	3	13.8	21	42.3	66	6	2
DFAS0470X03S060E	●	4.7	3	14.1	21	42.4	66	6	2
DFAS0480X03S060E	●	4.8	3	14.4	22	41.4	66	6	2
DFAS0490X03S060E	●	4.9	3	14.7	22	41.5	66	6	2
DFAS0500X03S060E	●	5	3	15	23	40.5	66	6	2

* DIN6537-K

DFAS-E - SOLID CARBIDE FLAT BOTTOM DRILLS, m7 TOLERANCE



Order number	DP102A	DC	L/D	LU	LCF	LS	OAL*	DCONMS	Type
DFAS0510X03S060E	●	5.1	3	15.3	25	38.6	66	6	2
DFAS0520X03S060E	●	5.2	3	15.6	25	38.6	66	6	2
DFAS0530X03S060E	●	5.3	3	15.9	25	38.7	66	6	2
DFAS0540X03S060E	●	5.4	3	16.2	25	38.7	66	6	2
DFAS0550X03S060E	●	5.5	3	16.5	25	38.8	66	6	2
DFAS0560X03S060E	●	5.6	3	16.8	26	37.8	66	6	2
DFAS0570X03S060E	●	5.7	3	17.1	26	37.9	66	6	2
DFAS0580X03S060E	●	5.8	3	17.4	27	36.9	66	6	2
DFAS0590X03S060E	●	5.9	3	17.7	27	37.0	66	6	2
DFAS0600X03S060E	●	6	3	18	27	37.0	66	6	1
DFAS0610X03S080E	●	6.1	3	18.3	29	47.1	79	8	2
DFAS0620X03S080E	●	6.2	3	18.6	29	47.1	79	8	2
DFAS0630X03S080E	●	6.3	3	18.9	29	47.2	79	8	2
DFAS0640X03S080E	●	6.4	3	19.2	29	47.2	79	8	2
DFAS0650X03S080E	●	6.5	3	19.5	29	47.3	79	8	2
DFAS0660X03S080E	●	6.6	3	19.8	30	46.3	79	8	2
DFAS0670X03S080E	●	6.7	3	20.1	30	46.4	79	8	2
DFAS0680X03S080E	●	6.8	3	20.4	32	44.4	79	8	2
DFAS0690X03S080E	●	6.9	3	20.7	32	44.5	79	8	2
DFAS0700X03S080E	●	7	3	21	32	44.5	79	8	2
DFAS0710X03S080E	●	7.1	3	21.3	34	42.6	79	8	2
DFAS0720X03S080E	●	7.2	3	21.6	34	42.6	79	8	2
DFAS0730X03S080E	●	7.3	3	21.9	34	42.7	79	8	2
DFAS0740X03S080E	●	7.4	3	22.2	34	42.7	79	8	2
DFAS0750X03S080E	●	7.5	3	22.5	34	42.8	79	8	2
DFAS0760X03S080E	●	7.6	3	22.8	36	40.8	79	8	2
DFAS0770X03S080E	●	7.7	3	23.1	36	40.9	79	8	2
DFAS0780X03S080E	●	7.8	3	23.4	36	40.9	79	8	2
DFAS0790X03S080E	●	7.9	3	23.7	36	41.0	79	8	2
DFAS0800X03S080E	●	8	3	24	36	41.0	79	8	1
DFAS0810X03S100E	●	8.1	3	24.3	39	47.1	89	10	2
DFAS0820X03S100E	●	8.2	3	24.6	39	47.1	89	10	2
DFAS0830X03S100E	●	8.3	3	24.9	39	47.2	89	10	2
DFAS0840X03S100E	●	8.4	3	25.2	39	47.2	89	10	2
DFAS0850X03S100E	●	8.5	3	25.5	39	47.3	89	10	2
DFAS0860X03S100E	●	8.6	3	25.8	40	46.3	89	10	2
DFAS0870X03S100E	●	8.7	3	26.1	40	46.4	89	10	2
DFAS0880X03S100E	●	8.8	3	26.4	40	46.4	89	10	2
DFAS0890X03S100E	●	8.9	3	26.7	40	46.5	89	10	2
DFAS0900X03S100E	●	9	3	27	40	46.5	89	10	2
DFAS0910X03S100E	●	9.1	3	27.3	43	43.6	89	10	2
DFAS0920X03S100E	●	9.2	3	27.6	43	43.6	89	10	2
DFAS0930X03S100E	●	9.3	3	27.9	43	43.7	89	10	2
DFAS0940X03S100E	●	9.4	3	28.2	43	43.7	89	10	2
DFAS0950X03S100E	●	9.5	3	28.5	43	43.8	89	10	2
DFAS0960X03S100E	●	9.6	3	28.8	45	41.8	89	10	2
DFAS0970X03S100E	●	9.7	3	29.1	45	41.9	89	10	2
DFAS0980X03S100E	●	9.8	3	29.4	45	41.9	89	10	2

2/3

* DIN6537-K



DFAS-E – SOLID CARBIDE FLAT BOTTOM DRILLS, m7 TOLERANCE



Order number	DP102A	DC	L/D	LU	LCF	LS	OAL*	DCONMS	Type
DFAS0990X03S100E	●	9.9	3	29.7	45	42.0	89	10	2
DFAS1000X03S100E	●	10	3	30	45	42.0	89	10	1
DFAS1010X03S120E	●	10.1	3	30.3	47	53.0	102	12	1
DFAS1020X03S120E	●	10.2	3	30.6	47	53.0	102	12	1
DFAS1030X03S120E	●	10.3	3	30.9	47	53.0	102	12	1
DFAS1040X03S120E	●	10.4	3	31.2	47	53.0	102	12	1
DFAS1050X03S120E	●	10.5	3	31.5	47	53.0	102	12	1
DFAS1060X03S120E	●	10.6	3	31.8	49	51.0	102	12	1
DFAS1070X03S120E	●	10.7	3	32.1	49	51.0	102	12	1
DFAS1080X03S120E	●	10.8	3	32.4	49	51.0	102	12	1
DFAS1090X03S120E	●	10.9	3	32.7	49	51.0	102	12	1
DFAS1100X03S120E	●	11	3	33	49	51.0	102	12	1
DFAS1110X03S120E	●	11.1	3	33.3	52	48.0	102	12	1
DFAS1120X03S120E	●	11.2	3	33.6	52	48.0	102	12	1
DFAS1130X03S120E	●	11.3	3	33.9	52	48.0	102	12	1
DFAS1140X03S120E	●	11.4	3	34.2	52	48.0	102	12	1
DFAS1150X03S120E	●	11.5	3	34.5	52	48.0	102	12	1
DFAS1160X03S120E	●	11.6	3	34.8	54	46.0	102	12	1
DFAS1170X03S120E	●	11.7	3	35.1	54	46.0	102	12	1
DFAS1180X03S120E	●	11.8	3	35.4	54	46.0	102	12	1
DFAS1190X03S120E	●	11.9	3	35.7	54	46.0	102	12	1
DFAS1200X03S120E	●	12	3	36	54	46.0	102	12	1
DFAS1250X03S140E	●	12.5	3	37.5	56	49.0	107	14	1
DFAS1300X03S140E	●	13	3	39	58	47.0	107	14	1
DFAS1350X03S140E	●	13.5	3	40.5	60	45.0	107	14	1
DFAS1400X03S140E	●	14	3	42	60	45.0	107	14	1

3/3


* DIN6537-K



DFAS



SOLID CARBIDE FLAT BOTTOM DRILLS h8 TOLERANCE



	DC=3	3<DC≤6	6<DC≤10	10<DC≤14
	0 -0.014	0 -0.018	0 -0.022	0 -0.027
	4<DCONMS≤6	6<DCONMS≤10	10<DCONMS≤14	
	0 -0.008	0 -0.009	0 -0.011	

Order number	DP102A	DC	L/D	LU	LCF	LS	OAL	DCONMS
DFAS0300X03S040	●	3.0	3	9.0	14	39.0	55	4
NEW DFAS0300X05S040	●	3.0	5	15.0	20	65.0	87	4
DFAS0310X03S040	★	3.1	3	9.3	16	37.0	55	4
NEW DFAS0310X05S040	●	3.1	5	15.5	23	62.0	87	4
DFAS0320X03S040	★	3.2	3	9.6	16	37.0	55	4
NEW DFAS0320X05S040	●	3.2	5	16.0	23	62.0	87	4
DFAS0330X03S040	●	3.3	3	9.9	16	37.0	55	4
NEW DFAS0330X05S040	●	3.3	5	16.5	23	62.0	87	4
DFAS0340X03S040	★	3.4	3	10.2	16	37.0	55	4
NEW DFAS0340X05S040	●	3.4	5	17.0	23	62.0	87	4
DFAS0350X03S040	●	3.5	3	10.5	16	37.0	55	4
NEW DFAS0350X05S040	●	3.5	5	17.5	23	62.0	87	4
DFAS0360X03S040	★	3.6	3	10.8	18	35.0	55	4
NEW DFAS0360X05S040	●	3.6	5	18.0	26	64.0	92	4
DFAS0370X03S040	★	3.7	3	11.1	18	35.0	55	4
NEW DFAS0370X05S040	●	3.7	5	18.5	26	64.0	92	4
DFAS0380X03S040	★	3.8	3	11.4	18	35.0	55	4
NEW DFAS0380X05S040	●	3.8	5	19.0	26	64.0	92	4
DFAS0390X03S040	★	3.9	3	11.7	18	35.0	55	4
NEW DFAS0390X05S040	●	3.9	5	19.5	26	64.0	92	4
DFAS0400X03S040	●	4.0	3	12.0	18	35.0	55	4
NEW DFAS0400X05S040	●	4.0	5	20.0	26	64.0	92	4
DFAS0410X03S050	★	4.1	3	12.3	20	40.0	62	5
NEW DFAS0410X05S050	●	4.1	5	20.5	29	69.0	100	5

1/5



DFAS – SOLID CARBIDE FLAT BOTTOM DRILLS, h8 TOLERANCE

Order number	DP102A	DC	L/D	LU	LCF	LS	OAL	DCONMS
DFAS0420X03S050	●	4.2	3	12.6	20	40.0	62	5
NEW DFAS0420X05S050	●	4.2	5	21.0	29	69.0	100	5
DFAS0430X03S050	★	4.3	3	12.9	20	40.0	62	5
NEW DFAS0430X05S050	●	4.3	5	21.5	29	69.0	100	5
DFAS0440X03S050	★	4.4	3	13.2	20	40.0	62	5
NEW DFAS0440X05S050	●	4.4	5	22.0	29	69.0	100	5
DFAS0450X03S050	●	4.5	3	13.5	20	40.0	62	5
NEW DFAS0450X05S050	●	4.5	5	22.5	29	69.0	100	5
DFAS0460X03S050	★	4.6	3	13.8	23	37.0	62	5
NEW DFAS0460X05S050	●	4.6	5	23.0	33	70.0	105	5
DFAS0470X03S050	★	4.7	3	14.1	23	37.0	62	5
NEW DFAS0470X05S050	●	4.7	5	23.5	33	70.0	105	5
DFAS0480X03S050	★	4.8	3	14.4	23	37.0	62	5
NEW DFAS0480X05S050	●	4.8	5	24.0	33	70.0	105	5
DFAS0490X03S050	★	4.9	3	14.7	23	37.0	62	5
NEW DFAS0490X05S050	●	4.9	5	24.5	33	70.0	105	5
DFAS0500X03S050	●	5.0	3	15.0	23	37.0	62	5
NEW DFAS0500X05S050	●	5.0	5	25.0	33	70.0	105	5
DFAS0510X03S060	★	5.1	3	15.3	25	39.0	66	6
NEW DFAS0510X05S060	●	5.1	5	25.5	36	62.0	100	6
DFAS0520X03S060	★	5.2	3	15.6	25	39.0	66	6
NEW DFAS0520X05S060	●	5.2	5	26.0	36	62.0	100	6
DFAS0530X03S060	●	5.3	3	15.9	25	39.0	66	6
NEW DFAS0530X05S060	●	5.3	5	26.5	36	62.0	100	6
DFAS0540X03S060	★	5.4	3	16.2	25	39.0	66	6
NEW DFAS0540X05S060	●	5.4	5	27.0	36	62.0	100	6
DFAS0550X03S060	●	5.5	3	16.5	25	39.0	66	6
NEW DFAS0550X05S060	●	5.5	5	27.5	36	62.0	100	6
DFAS0560X03S060	★	5.6	3	16.8	27	37.0	66	6
NEW DFAS0560X05S060	●	5.6	5	28.0	39	59.0	100	6
DFAS0570X03S060	★	5.7	3	17.1	27	37.0	66	6
NEW DFAS0570X05S060	●	5.7	5	28.5	39	59.0	100	6
DFAS0580X03S060	★	5.8	3	17.4	27	37.0	66	6
NEW DFAS0580X05S060	●	5.8	5	29.0	39	59.0	100	6
DFAS0590X03S060	★	5.9	3	17.7	27	37.0	66	6
NEW DFAS0590X05S060	●	5.9	5	29.5	39	59.0	100	6
DFAS0600X03S060	●	6.0	3	18.0	27	37.0	66	6
NEW DFAS0600X05S060	●	6.0	5	30.0	39	59.0	100	6
DFAS0610X03S070	★	6.1	3	18.3	29	44.0	75	7
NEW DFAS0610X05S070	●	6.1	5	30.5	42	65.0	109	7
DFAS0620X03S070	★	6.2	3	18.6	29	44.0	75	7
NEW DFAS0620X05S070	●	6.2	5	31.0	42	65.0	109	7
DFAS0630X03S070	★	6.3	3	18.9	29	44.0	75	7
NEW DFAS0630X05S070	●	6.3	5	31.5	42	65.0	109	7
DFAS0640X03S070	★	6.4	3	19.2	29	44.0	75	7
NEW DFAS0640X05S070	●	6.4	5	32.0	42	65.0	109	7
DFAS0650X03S070	●	6.5	3	19.5	29	44.0	75	7
NEW DFAS0650X05S070	●	6.5	5	32.5	42	65.0	109	7

2/5



DFAS – SOLID CARBIDE FLAT BOTTOM DRILLS, h8 TOLERANCE

Order number	DP102A	DC	L/D	LU	LCF	LS	OAL	DCONMS
DFAS0660X03S070	★	6.6	3	19.8	32	41.0	75	7
NEW DFAS0660X05S070	●	6.6	5	33.0	46	61.0	109	7
DFAS0670X03S070	★	6.7	3	20.1	32	41.0	75	7
NEW DFAS0670X05S070	●	6.7	5	33.5	46	61.0	109	7
DFAS0680X03S070	●	6.8	3	20.4	32	41.0	75	7
NEW DFAS0680X05S070	●	6.8	5	34.0	46	61.0	109	7
DFAS0690X03S070	★	6.9	3	20.7	32	41.0	75	7
NEW DFAS0690X05S070	●	6.9	5	34.5	46	61.0	109	7
DFAS0700X03S070	●	7.0	3	21.0	32	41.0	75	7
NEW DFAS0700X05S070	●	7.0	5	35.0	46	61.0	109	7
DFAS0710X03S080	★	7.1	3	21.3	34	44.0	80	8
NEW DFAS0710X05S080	●	7.1	5	35.5	49	67.0	118	8
DFAS0720X03S080	★	7.2	3	21.6	34	44.0	80	8
NEW DFAS0720X05S080	●	7.2	5	36.0	49	67.0	118	8
DFAS0730X03S080	★	7.3	3	21.9	34	44.0	80	8
NEW DFAS0730X05S080	●	7.3	5	36.5	49	67.0	118	8
DFAS0740X03S080	★	7.4	3	22.2	34	44.0	80	8
NEW DFAS0740X05S080	●	7.4	5	37.0	49	67.0	118	8
DFAS0750X03S080	●	7.5	3	22.5	34	44.0	80	8
NEW DFAS0750X05S080	●	7.5	5	37.5	49	67.0	118	8
DFAS0760X03S080	★	7.6	3	22.8	36	42.0	80	8
NEW DFAS0760X05S080	●	7.6	5	38.0	52	64.0	118	8
DFAS0770X03S080	★	7.7	3	23.1	36	42.0	80	8
NEW DFAS0770X05S080	●	7.7	5	38.5	52	64.0	118	8
DFAS0780X03S080	★	7.8	3	23.4	36	42.0	80	8
NEW DFAS0780X05S080	●	7.8	5	39.0	52	64.0	118	8
DFAS0790X03S080	★	7.9	3	23.7	36	42.0	80	8
NEW DFAS0790X05S080	●	7.9	5	39.5	52	64.0	118	8
DFAS0800X03S080	●	8.0	3	24.0	36	42.0	80	8
NEW DFAS0800X05S080	●	8.0	5	40.0	52	64.0	118	8
DFAS0810X03S090	★	8.1	3	24.3	38	45.0	85	9
NEW DFAS0810X05S090	●	8.1	5	40.5	55	70.0	127	9
DFAS0820X03S090	●	8.2	3	24.6	38	45.0	85	9
NEW DFAS0820X05S090	●	8.2	5	41.0	55	70.0	127	9
DFAS0830X03S090	★	8.3	3	24.9	38	45.0	85	9
NEW DFAS0830X05S090	●	8.3	5	41.5	55	70.0	127	9
DFAS0840X03S090	★	8.4	3	25.2	38	45.0	85	9
NEW DFAS0840X05S090	●	8.4	5	42.0	55	70.0	127	9
DFAS0850X03S090	●	8.5	3	25.5	38	45.0	85	9
NEW DFAS0850X05S090	●	8.5	5	42.5	55	70.0	127	9
DFAS0860X03S090	★	8.6	3	25.8	41	42.0	85	9
NEW DFAS0860X05S090	●	8.6	5	43.0	59	66.0	127	9
DFAS0870X03S090	★	8.7	3	26.1	41	42.0	85	9
NEW DFAS0870X05S090	●	8.7	5	43.5	59	66.0	127	9
DFAS0880X03S090	●	8.8	3	26.4	41	42.0	85	9
NEW DFAS0880X05S090	●	8.8	5	44.0	59	66.0	127	9
DFAS0890X03S090	★	8.9	3	26.7	41	42.0	85	9
NEW DFAS0890X05S090	●	8.9	5	44.5	59	66.0	127	9

3/5



DFAS – SOLID CARBIDE FLAT BOTTOM DRILLS, h8 TOLERANCE

Order number	DP102A	DC	L/D	LU	LCF	LS	OAL	DCONMS
DFAS0900X03S090	●	9.0	3	27.0	41	42.0	85	9
NEW DFAS0900X05S090	●	9.0	5	45.0	59	66.0	127	9
DFAS0910X03S100	★	9.1	3	27.3	43	45.0	90	10
NEW DFAS0910X05S100	●	9.1	5	45.5	62	72.0	136	10
DFAS0920X03S100	★	9.2	3	27.6	43	45.0	90	10
NEW DFAS0920X05S100	●	9.2	5	46.0	62	72.0	136	10
DFAS0930X03S100	★	9.3	3	27.9	43	45.0	90	10
NEW DFAS0930X05S100	●	9.3	5	46.5	62	72.0	136	10
DFAS0940X03S100	★	9.4	3	28.2	43	45.0	90	10
NEW DFAS0940X05S100	●	9.4	5	47.0	62	72.0	136	10
DFAS0950X03S100	●	9.5	3	28.5	43	45.0	90	10
NEW DFAS0950X05S100	●	9.5	5	47.5	62	72.0	136	10
DFAS0960X03S100	★	9.6	3	28.8	45	43.0	90	10
NEW DFAS0960X05S100	●	9.6	5	48.0	65	69.0	136	10
DFAS0970X03S100	●	9.7	3	29.1	45	43.0	90	10
NEW DFAS0970X05S100	●	9.7	5	48.5	65	69.0	136	10
DFAS0980X03S100	★	9.8	3	29.4	45	43.0	90	10
NEW DFAS0980X05S100	●	9.8	5	49.0	65	69.0	136	10
DFAS0990X03S100	★	9.9	3	29.7	45	43.0	90	10
NEW DFAS0990X05S100	●	9.9	5	49.5	65	69.0	136	10
DFAS1000X03S100	●	10.0	3	30.0	45	43.0	90	10
NEW DFAS1000X05S100	●	10.0	5	50.0	65	69.0	136	10
DFAS1010X03S110	★	10.1	3	30.3	47	52.0	101	11
NEW DFAS1010X05S110	●	10.1	5	50.5	68	79.0	149	11
DFAS1020X03S110	●	10.2	3	30.6	47	52.0	101	11
NEW DFAS1020X05S110	●	10.2	5	51.0	68	79.0	149	11
DFAS1030X03S110	★	10.3	3	30.9	47	52.0	101	11
NEW DFAS1030X05S110	●	10.3	5	51.5	68	79.0	149	11
DFAS1040X03S110	★	10.4	3	31.2	47	52.0	101	11
NEW DFAS1040X05S110	●	10.4	5	52.0	68	79.0	149	11
DFAS1050X03S110	●	10.5	3	31.5	47	52.0	101	11
NEW DFAS1050X05S110	●	10.5	5	52.5	68	79.0	149	11
DFAS1060X03S110	★	10.6	3	31.8	50	49.0	101	11
NEW DFAS1060X05S110	●	10.6	5	53.0	72	75.0	149	11
DFAS1070X03S110	★	10.7	3	32.1	50	49.0	101	11
NEW DFAS1070X05S110	●	10.7	5	53.5	72	75.0	149	11
DFAS1080X03S110	★	10.8	3	32.4	50	49.0	101	11
NEW DFAS1080X05S110	●	10.8	5	54.0	72	75.0	149	11
DFAS1090X03S110	★	10.9	3	32.7	50	49.0	101	11
NEW DFAS1090X05S110	●	10.9	5	54.5	72	75.0	149	11
DFAS1100X03S110	●	11.0	3	33.0	50	49.0	101	11
NEW DFAS1100X05S110	●	11.0	5	55.0	72	75.0	149	11
DFAS1110X03S120	★	11.1	3	33.3	52	51.0	105	12
NEW DFAS1110X05S120	●	11.1	5	55.5	75	81.0	158	12
DFAS1120X03S120	★	11.2	3	33.6	52	51.0	105	12
NEW DFAS1120X05S120	●	11.2	5	56.0	75	81.0	158	12
DFAS1130X03S120	★	11.3	3	33.9	52	51.0	105	12

4/5



DFAS – SOLID CARBIDE FLAT BOTTOM DRILLS, h8 TOLERANCE

	Order number	DP102A	DC	L/D	LU	LCF	LS	OAL	DCONMS
NEW	DFAS1130X05S120	●	11.3	5	56.5	75	81.0	158	12
	DFAS1140X03S120	★	11.4	3	34.2	52	51.0	105	12
NEW	DFAS1140X05S120	●	11.4	5	57.0	75	81.0	158	12
	DFAS1150X03S120	●	11.5	3	34.5	52	51.0	105	12
NEW	DFAS1150X05S120	●	11.5	5	57.5	75	81.0	158	12
	DFAS1160X03S120	★	11.6	3	34.8	54	49.0	105	12
NEW	DFAS1160X05S120	●	11.6	5	58.0	78	78.0	158	12
	DFAS1170X03S120	★	11.7	3	35.1	54	49.0	105	12
NEW	DFAS1170X05S120	●	11.7	5	58.5	78	78.0	158	12
	DFAS1180X03S120	★	11.8	3	35.4	54	49.0	105	12
NEW	DFAS1180X05S120	●	11.8	5	59.0	78	78.0	158	12
	DFAS1190X03S120	★	11.9	3	35.7	54	49.0	105	12
NEW	DFAS1190X05S120	●	11.9	5	59.5	78	78.0	158	12
	DFAS1200X03S120	●	12.0	3	36.0	54	49.0	105	12
NEW	DFAS1200X05S120	●	12.0	5	60.0	78	78.0	158	12
	DFAS1250X03S130	★	12.5	3	37.5	56	52.0	110	13
NEW	DFAS1250X05S130	●	12.5	5	62.5	81	84.0	167	13
	DFAS1300X03S130	●	13.0	3	39.0	59	49.0	110	13
NEW	DFAS1300X05S130	●	13.0	5	65.0	85	80.0	167	13
	DFAS1350X03S140	★	13.5	3	40.5	61	51.0	114	14
NEW	DFAS1350X05S140	●	13.5	5	67.5	88	86.0	176	14
	DFAS1400X03S140	●	14.0	3	42.0	63	49.0	114	14
NEW	DFAS1400X05S140	●	14.0	5	70.0	91	83.0	176	14

5/5




DFAS / DFAS-E

RECOMMENDED CUTTING CONDITIONS

Material	DC	L/D	n	$\alpha = 0^\circ$ fr	
P Mild steel, Carbon steel, Alloy steel	3.0	≤5	10610	0.07 [0.04 – 0.10]	
	4.0	≤5	7960	0.08 [0.04 – 0.11]	
	5.0	≤5	6370	0.10 [0.05 – 0.14]	
	6.0	≤5	5310	0.12 [0.06 – 0.17]	
	7.0	≤5	4550	0.13 [0.07 – 0.20]	
	8.0	≤5	3980	0.16 [0.08 – 0.23]	
	9.0	≤5	3540	0.17 [0.09 – 0.26]	
	10.0	≤5	3180	0.20 [0.10 – 0.29]	
	11.0	≤5	2890	0.22 [0.11 – 0.32]	
	12.0	≤5	2650	0.24 [0.12 – 0.35]	
	13.0	≤5	2450	0.26 [0.13 – 0.39]	
	14.0	≤5	2270	0.28 [0.14 – 0.42]	
	M Stainless Steel	3.0	≤5	3180	0.04 [0.01 – 0.08]
		4.0	≤5	2390	0.06 [0.01 – 0.11]
5.0		≤5	1910	0.08 [0.02 – 0.13]	
6.0		≤5	1590	0.08 [0.02 – 0.15]	
7.0		≤5	1360	0.09 [0.02 – 0.16]	
8.0		≤5	1190	0.10 [0.03 – 0.17]	
9.0		≤5	1060	0.11 [0.03 – 0.19]	
10.0		≤5	950	0.12 [0.03 – 0.20]	
11.0		≤5	870	0.13 [0.04 – 0.22]	
12.0		≤5	800	0.14 [0.04 – 0.24]	
13.0		≤5	730	0.15 [0.04 – 0.26]	
14.0		≤5	680	0.16 [0.05 – 0.28]	
K Gray cast iron, Ductile cast iron		3.0	≤5	10610	0.04 [0.02 – 0.07]
		4.0	≤5	7960	0.05 [0.03 – 0.09]
	5.0	≤5	6370	0.07 [0.03 – 0.11]	
	6.0	≤5	5310	0.08 [0.04 – 0.13]	
	7.0	≤5	4550	0.09 [0.05 – 0.15]	
	8.0	≤5	3980	0.11 [0.05 – 0.17]	
	9.0	≤5	3540	0.12 [0.06 – 0.20]	
	10.0	≤5	3180	0.13 [0.07 – 0.22]	
	11.0	≤5	2890	0.15 [0.07 – 0.24]	
	12.0	≤5	2650	0.16 [0.08 – 0.26]	
	13.0	≤5	2450	0.17 [0.09 – 0.28]	
	14.0	≤5	2270	0.19 [0.09 – 0.30]	

1/2

1. This should be the depth from the uppermost surface of the workpiece material when machining on an angled surface. (Refer to diagram)
2. The cutting table above assumes drilling on a flat surface.
For hole drilling on an angled surface, adjust the feed rate in accordance with the inclination angle.
When the inclination angle α is 30° or less, reduce the feed rate by 30 % or more as a guideline.
When the inclination angle α is greater than 30° , reduce the feed rate by 50 % or more as a guideline.
3. This product is a tool intended for hole drilling. It cannot be used for cross-feed or helical machining.
4. If a drill with $L/D = 5$ is used, a pilot hole of the same diameter, or a centre drilled hole with a diameter larger than the finished drill is needed.




DFAS / DFAS-E

Material	DC	L/D	n	$\alpha = 0^\circ$ fr	
N Aluminium alloy	3.0	≤ 5	13790	0.04 (0.02 – 0.07)	
	4.0	≤ 5	10350	0.05 (0.03 – 0.09)	
	5.0	≤ 5	8280	0.07 (0.03 – 0.11)	
	6.0	≤ 5	6900	0.08 (0.04 – 0.13)	
	7.0	≤ 5	5910	0.09 (0.05 – 0.15)	
	8.0	≤ 5	5170	0.11 (0.05 – 0.17)	
	9.0	≤ 5	4600	0.12 (0.06 – 0.20)	
	10.0	≤ 5	4140	0.13 (0.07 – 0.22)	
	11.0	≤ 5	3760	0.15 (0.07 – 0.24)	
	12.0	≤ 5	3450	0.16 (0.08 – 0.26)	
	13.0	≤ 5	3180	0.17 (0.09 – 0.28)	
	14.0	≤ 5	2960	0.19 (0.09 – 0.30)	
	S Titanium alloy	3.0	≤ 5	3710	0.03 (0.01 – 0.05)
		4.0	≤ 5	2790	0.04 (0.01 – 0.07)
5.0		≤ 5	2230	0.05 (0.02 – 0.08)	
6.0		≤ 5	1860	0.06 (0.02 – 0.10)	
7.0		≤ 5	1590	0.07 (0.02 – 0.12)	
8.0		≤ 5	1390	0.08 (0.03 – 0.13)	
9.0		≤ 5	1240	0.09 (0.03 – 0.15)	
10.0		≤ 5	1110	0.10 (0.03 – 0.17)	
11.0		≤ 5	1010	0.11 (0.04 – 0.18)	
12.0		≤ 5	930	0.12 (0.04 – 0.20)	
13.0		≤ 5	860	0.13 (0.04 – 0.22)	
14.0		≤ 5	800	0.14 (0.05 – 0.23)	

2/2

1. This should be the depth from the uppermost surface of the workpiece material when machining on an angled surface. (Refer to diagram)
2. The cutting table above assumes drilling on a flat surface.
For hole drilling on an angled surface, adjust the feed rate in accordance with the inclination angle.
When the inclination angle α is 30° or less, reduce the feed rate by 30 % or more as a guideline.
When the inclination angle α is greater than 30° , reduce the feed rate by 50 % or more as a guideline.
3. This product is a tool intended for hole drilling. It cannot be used for cross-feed or helical machining.
4. If a drill with $L/D = 5$ is used, a pilot hole of the same diameter, or a centre drilled hole with a diameter larger than the finished drill is needed.




MINI-MFE



FOR SMALL DIAMETER HOLES
DC 0.75 – 2.95

P M K N



$0.75 \leq DC \leq 2.95$

0

-0.014



DCONMS = 3 DCONMS = 4

0

-0.006

0

-0.008

Order number	DP102A	DC	L/D	LU	LCF	LS	OAL	DCONMS
MFE0075X02S030	★	0.75	2	1.5	3.0	37.3	45	3
MFE0080X02S030	★	0.80	2	1.6	3.2	37.2	45	3
MFE0085X02S030	★	0.85	2	1.7	3.4	37.1	45	3
MFE0090X02S030	★	0.90	2	1.8	3.6	37.0	45	3
MFE0095X02S030	★	0.95	2	1.9	3.8	36.9	45	3
MFE0100X02S030	★	1.00	2	2.0	4.0	36.8	45	3
MFE0105X02S030	★	1.05	2	2.1	4.2	36.7	45	3
MFE0110X02S030	★	1.10	2	2.2	4.4	36.6	45	3
MFE0115X02S030	★	1.15	2	2.3	4.6	36.4	45	3
MFE0120X02S030	★	1.20	2	2.4	4.8	36.3	45	3
MFE0125X02S030	★	1.25	2	2.5	5.0	36.2	45	3
MFE0130X02S030	★	1.30	2	2.6	5.2	36.1	45	3
MFE0135X02S030	★	1.35	2	2.7	5.4	36.0	45	3
MFE0140X02S030	★	1.40	2	2.8	5.6	35.9	45	3
MFE0145X02S030	★	1.45	2	2.9	5.8	35.8	45	3
MFE0150X02S030	★	1.50	2	3.0	6.0	35.7	45	3
MFE0155X02S030	★	1.55	2	3.1	6.2	35.6	45	3
MFE0160X02S030	★	1.60	2	3.2	6.4	35.5	45	3
MFE0165X02S030	★	1.65	2	3.3	6.6	35.4	45	3
MFE0170X02S030	★	1.70	2	3.4	6.8	35.3	45	3
MFE0175X02S030	★	1.75	2	3.5	7.0	35.2	45	3

1/2

MINI-MFE – FOR SMALL DIAMETER HOLES, DC 0.75 – 2.95

Order number	DP102A	DC	L/D	LU	LCF	LS	OAL	DCONMS
MFE0180X02S030	★	1.80	2	3.6	7.2	35.1	45	3
MFE0185X02S030	★	1.85	2	3.7	7.4	35.0	45	3
MFE0190X02S030	★	1.90	2	3.8	7.6	34.8	45	3
MFE0195X02S030	★	1.95	2	3.9	7.8	34.7	45	3
MFE0200X02S040	★	2.00	2	4.0	8.0	37.8	50	4
MFE0205X02S040	★	2.05	2	4.1	8.2	37.7	50	4
MFE0210X02S040	★	2.10	2	4.2	8.4	37.6	50	4
MFE0215X02S040	★	2.15	2	4.3	8.6	37.4	50	4
MFE0220X02S040	★	2.20	2	4.4	8.8	37.3	50	4
MFE0225X02S040	★	2.25	2	4.5	9.0	37.2	50	4
MFE0230X02S040	★	2.30	2	4.6	9.2	37.1	50	4
MFE0235X02S040	★	2.35	2	4.7	9.4	37.0	50	4
MFE0240X02S040	★	2.40	2	4.8	9.6	36.9	50	4
MFE0245X02S040	★	2.45	2	4.9	9.8	36.8	50	4
MFE0250X02S040	★	2.50	2	5.0	10.0	36.7	50	4
MFE0255X02S040	★	2.55	2	5.1	10.2	36.6	50	4
MFE0260X02S040	★	2.60	2	5.2	10.4	36.5	50	4
MFE0265X02S040	★	2.65	2	5.3	10.6	36.4	50	4
MFE0270X02S040	★	2.70	2	5.4	10.8	36.3	50	4
MFE0275X02S040	★	2.75	2	5.5	11.0	36.2	50	4
MFE0280X02S040	★	2.80	2	5.6	11.2	36.1	50	4
MFE0285X02S040	★	2.85	2	5.7	11.4	36.0	50	4
MFE0290X02S040	★	2.90	2	5.8	11.6	35.8	50	4
MFE0295X02S040	★	2.95	2	5.9	11.8	35.7	50	4

2/2





MFE



SOLID CARBIDE FLAT BOTTOM DRILLS h7 TOLERANCE

P **M** **K** **N**



$3 < DC \leq 6$	$6 < DC \leq 10$	$10 < DC \leq 18$	$18 < DC \leq 20$
0	0	0	0
-0.012	-0.015	-0.018	-0.021




DCONMS = 6	$6 < DCONMS \leq 10$	$10 < DCONMS \leq 18$	DCONMS = 20
0	0	0	0
-0.008	-0.009	-0.011	-0.013

Order number	DP1020	DC	L/D	LU	LCF	LS	OAL	DCONMS	Type
MFE0300X02S060	★	3.0	2	6.0	12	35.4	55	6	1
MFE0310X02S060	★	3.1	2	6.2	14	33.6	55	6	1
MFE0320X02S060	★	3.2	2	6.4	14	33.8	55	6	1
MFE0330X02S060	★	3.3	2	6.6	14	34.0	55	6	1
MFE0340X02S060	★	3.4	2	6.8	14	34.1	55	6	1
MFE0350X02S060	★	3.5	2	7.0	14	34.3	55	6	1
MFE0360X02S060	★	3.6	2	7.2	16	32.5	55	6	1
MFE0370X02S060	★	3.7	2	7.4	16	32.7	55	6	1
MFE0380X02S060	★	3.8	2	7.6	16	32.9	55	6	1
MFE0390X02S060	★	3.9	2	7.8	16	33.1	55	6	1
MFE0400X02S060	★	4.0	2	8.0	16	33.3	55	6	1
MFE0410X02S060	★	4.1	2	8.2	18	38.5	62	6	1
MFE0420X02S060	★	4.2	2	8.4	18	38.6	62	6	1
MFE0430X02S060	★	4.3	2	8.6	18	38.8	62	6	1
MFE0440X02S060	★	4.4	2	8.8	18	39.0	62	6	1
MFE0450X02S060	★	4.5	2	9.0	18	39.2	62	6	1
MFE0460X02S060	★	4.6	2	9.2	20	38.3	62	6	1
MFE0470X02S060	★	4.7	2	9.4	20	38.3	62	6	1
MFE0480X02S060	★	4.8	2	9.6	20	38.4	62	6	1
MFE0490X02S060	★	4.9	2	9.8	20	38.4	62	6	1
MFE0500X02S060	★	5.0	2	10.0	20	38.5	62	6	1

MFE - SOLID CARBIDE FLAT BOTTOM DRILLS, h7 TOLERANCE

Order number	DP1020	DC	L/D	LU	LCF	LS	OAL	DCONMS	Type
MFE0510X02S060	★	5.1	2	10.2	22	36.5	62	6	1
MFE0520X02S060	★	5.2	2	10.4	22	36.6	62	6	1
MFE0530X02S060	★	5.3	2	10.6	22	36.6	62	6	1
MFE0540X02S060	★	5.4	2	10.8	22	36.7	62	6	1
MFE0550X02S060	★	5.5	2	11.0	22	36.7	62	6	1
MFE0560X02S060	★	5.6	2	11.2	24	34.8	62	6	1
MFE0570X02S060	★	5.7	2	11.4	24	34.8	62	6	1
MFE0580X02S060	★	5.8	2	11.6	24	34.9	62	6	1
MFE0590X02S060	★	5.9	2	11.8	24	34.9	62	6	1
MFE0600X02S060	★	6.0	2	12.0	24	35.0	62	6	1
MFE0610X02S070	★	6.1	2	12.2	26	44.5	74	7	1
MFE0610X02S080	★	6.1	2	12.2	26	44.0	74	8	1
MFE0620X02S070	★	6.2	2	12.4	26	44.6	74	7	1
MFE0620X02S080	★	6.2	2	12.4	26	44.1	74	8	1
MFE0630X02S070	★	6.3	2	12.6	26	44.6	74	7	1
MFE0630X02S080	★	6.3	2	12.6	26	44.1	74	8	1
MFE0640X02S070	★	6.4	2	12.8	26	44.7	74	7	1
MFE0640X02S080	★	6.4	2	12.8	26	44.2	74	8	1
MFE0650X02S070	★	6.5	2	13.0	26	44.7	74	7	1
MFE0650X02S080	★	6.5	2	13.0	26	44.2	74	8	1
MFE0660X02S070	★	6.6	2	13.2	28	42.8	74	7	1
MFE0660X02S080	★	6.6	2	13.2	28	42.3	74	8	1
MFE0670X02S070	★	6.7	2	13.4	28	42.8	74	7	1
MFE0670X02S080	★	6.7	2	13.4	28	42.3	74	8	1
MFE0680X02S070	★	6.8	2	13.6	28	42.9	74	7	1
MFE0680X02S080	★	6.8	2	13.6	28	42.4	74	8	1
MFE0690X02S070	★	6.9	2	13.8	28	42.9	74	7	1
MFE0690X02S080	★	6.9	2	13.8	28	42.4	74	8	1
MFE0700X02S070	★	7.0	2	14.0	28	43.0	74	7	1
MFE0700X02S080	★	7.0	2	14.0	28	42.5	74	8	1
MFE0710X02S080	★	7.1	2	14.2	30	40.5	74	8	1
MFE0720X02S080	★	7.2	2	14.4	30	40.6	74	8	1
MFE0730X02S080	★	7.3	2	14.6	30	40.6	74	8	1
MFE0740X02S080	★	7.4	2	14.8	30	40.7	74	8	1
MFE0750X02S080	★	7.5	2	15.0	30	40.7	74	8	1
MFE0760X02S080	★	7.6	2	15.2	32	38.8	74	8	1
MFE0770X02S080	★	7.7	2	15.4	32	38.8	74	8	1
MFE0780X02S080	★	7.8	2	15.6	32	38.9	74	8	1
MFE0790X02S080	★	7.9	2	15.8	32	38.9	74	8	1
MFE0800X02S080	★	8.0	2	16.0	32	39.0	74	8	1
MFE0810X02S100	★	8.1	2	16.2	34	46.0	84	10	1
MFE0820X02S100	★	8.2	2	16.4	34	46.1	84	10	1
MFE0830X02S100	★	8.3	2	16.6	34	46.1	84	10	1
MFE0840X02S100	★	8.4	2	16.8	34	46.2	84	10	1
MFE0850X02S100	★	8.5	2	17.0	34	46.2	84	10	1
MFE0860X02S100	★	8.6	2	17.2	36	44.3	84	10	1
MFE0870X02S100	★	8.7	2	17.4	36	44.3	84	10	1
MFE0880X02S100	★	8.8	2	17.6	36	44.4	84	10	1
MFE0890X02S100	★	8.9	2	17.8	36	44.4	84	10	1
MFE0900X02S100	★	9.0	2	18.0	36	44.5	84	10	1
MFE0910X02S100	★	9.1	2	18.2	38	42.5	84	10	1
MFE0920X02S100	★	9.2	2	18.4	38	42.6	84	10	1

MFE – SOLID CARBIDE FLAT BOTTOM DRILLS, h7 TOLERANCE



Order number	DP1020	DC	L/D	LU	LCF	LS	OAL	DCONMS	Type
MFE0930X02S100	★	9.3	2	18.6	38	42.6	84	10	1
MFE0940X02S100	★	9.4	2	18.8	38	42.7	84	10	1
MFE0950X02S100	★	9.5	2	19.0	38	42.7	84	10	1
MFE0960X02S100	★	9.6	2	19.2	40	40.8	84	10	1
MFE0970X02S100	★	9.7	2	19.4	40	40.8	84	10	1
MFE0980X02S100	★	9.8	2	19.6	40	40.9	84	10	1
MFE0990X02S100	★	9.9	2	19.8	40	40.9	84	10	1
MFE1000X02S100	★	10.0	2	20.0	40	41.0	84	10	1
MFE1010X02S120	★	10.1	2	20.2	42	49.0	95	12	1
MFE1020X02S120	★	10.2	2	20.4	42	49.1	95	12	1
MFE1030X02S120	★	10.3	2	20.6	42	49.1	95	12	1
MFE1040X02S120	★	10.4	2	20.8	42	49.2	95	12	1
MFE1050X02S120	★	10.5	2	21.0	42	49.2	95	12	1
MFE1060X02S120	★	10.6	2	21.2	44	47.3	95	12	1
MFE1070X02S120	★	10.7	2	21.4	44	47.3	95	12	1
MFE1080X02S120	★	10.8	2	21.6	44	47.4	95	12	1
MFE1090X02S120	★	10.9	2	21.8	44	47.4	95	12	1
MFE1100X02S120	★	11.0	2	22.0	44	47.5	95	12	1
MFE1110X02S120	★	11.1	2	22.2	46	45.5	95	12	1
MFE1120X02S120	★	11.2	2	22.4	46	45.6	95	12	1
MFE1130X02S120	★	11.3	2	22.6	46	45.6	95	12	1
MFE1140X02S120	★	11.4	2	22.8	46	45.7	95	12	1
MFE1150X02S120	★	11.5	2	23.0	46	45.7	95	12	1
MFE1160X02S120	★	11.6	2	23.2	48	43.8	95	12	1
MFE1170X02S120	★	11.7	2	23.4	48	43.8	95	12	1
MFE1180X02S120	★	11.8	2	23.6	48	43.9	95	12	1
MFE1190X02S120	★	11.9	2	23.8	48	43.9	95	12	1
MFE1200X02S120	★	12.0	2	24.0	48	44.0	95	12	1
MFE1250X02S140	★	12.5	2	25.0	50	49.0	102	14	2
MFE1300X02S140	★	13.0	2	26.0	52	47.0	102	14	2
MFE1350X02S140	★	13.5	2	27.0	54	45.0	102	14	2
MFE1400X02S140	★	14.0	2	28.0	56	43.0	102	14	2
MFE1450X02S160	★	14.5	2	29.0	58	50.0	111	16	2
MFE1500X02S160	★	15.0	2	30.0	60	48.0	111	16	2
MFE1550X02S160	★	15.5	2	31.0	62	46.0	111	16	2
MFE1600X02S160	★	16.0	2	32.0	64	44.0	111	16	2
MFE1650X02S180	★	16.5	2	33.0	66	50.0	119	18	2
MFE1700X02S180	★	17.0	2	34.0	68	48.0	119	18	2
MFE1750X02S180	★	17.5	2	35.0	70	46.0	119	18	2
MFE1800X02S180	★	18.0	2	36.0	72	44.0	119	18	2
MFE1850X02S200	★	18.5	2	37.0	74	50.0	127	20	2
MFE1900X02S200	★	19.0	2	38.0	76	48.0	127	20	2
MFE1950X02S200	★	19.5	2	39.0	78	46.0	127	20	2
MFE2000X02S200	★	20.0	2	40.0	80	44.0	127	20	2


MINI-MFE / MFE

RECOMMENDED CUTTING CONDITIONS

Material	Properties	DC	L/D	n	$\alpha = 0^\circ$ fr
Mild steel	<180HB	0.75	≤2	23300	0.030 (0.010 – 0.050)
		1.0	≤2	17500	0.030 (0.010 – 0.050)
		1.5	≤2	12200	0.035 (0.015 – 0.055)
		2.0	≤2	9500	0.040 (0.020 – 0.060)
		2.5	≤2	7900	0.050 (0.030 – 0.070)
		3.0	≤2	7900	0.060 (0.040 – 0.080)
		4.0	≤2	5900	0.080 (0.060 – 0.100)
		5.0	≤2	4700	0.100 (0.080 – 0.130)
		6.0	≤2	3900	0.130 (0.100 – 0.150)
		8.0	≤2	2900	0.150 (0.130 – 0.170)
		10.0	≤2	2300	0.170 (0.150 – 0.200)
		12.0	≤2	1900	0.200 (0.170 – 0.250)
		16.0	≤2	1400	0.250 (0.200 – 0.300)
20.0	≤2	1100	0.300 (0.250 – 0.350)		
Carbon steel, Alloy steel	180 – 280HB	0.75	≤2	19000	0.030 (0.010 – 0.050)
		1.0	≤2	14300	0.030 (0.010 – 0.050)
		1.5	≤2	10000	0.035 (0.015 – 0.055)
		2.0	≤2	7900	0.040 (0.020 – 0.060)
		2.5	≤2	6600	0.050 (0.030 – 0.070)
		3.0	≤2	7900	0.060 (0.040 – 0.080)
		4.0	≤2	5900	0.080 (0.060 – 0.100)
		5.0	≤2	4700	0.100 (0.080 – 0.130)
		6.0	≤2	3900	0.130 (0.100 – 0.150)
		8.0	≤2	2900	0.150 (0.130 – 0.170)
		10.0	≤2	2300	0.170 (0.150 – 0.200)
		12.0	≤2	1900	0.200 (0.170 – 0.250)
		16.0	≤2	1400	0.250 (0.200 – 0.300)
20.0	≤2	1100	0.300 (0.250 – 0.350)		
Carbon steel, Alloy steel	280 – 350HB	0.75	≤2	16900	0.030 (0.010 – 0.050)
		1.0	≤2	12700	0.030 (0.010 – 0.050)
		1.5	≤2	8400	0.035 (0.015 – 0.050)
		2.0	≤2	6700	0.040 (0.020 – 0.060)
		2.5	≤2	5700	0.050 (0.030 – 0.070)
		3.0	≤2	6800	0.060 (0.040 – 0.080)
		4.0	≤2	5100	0.080 (0.060 – 0.100)
		5.0	≤2	4100	0.100 (0.080 – 0.130)
		6.0	≤2	3400	0.130 (0.100 – 0.150)
		8.0	≤2	2500	0.150 (0.130 – 0.170)
		10.0	≤2	2000	0.170 (0.150 – 0.200)
		12.0	≤2	1700	0.200 (0.170 – 0.250)
		16.0	≤2	1200	0.250 (0.200 – 0.300)
20.0	≤2	1000	0.300 (0.250 – 0.350)		

1/2

1. The recommended hole depth is DC x 2. This should be the depth from the uppermost surface of the workpiece when machining on an angled surface. (Refer to diagram)
2. The above cutting table assumes drilling on a flat surface.
For hole drilling on an angled surface, adjust the feed rate in accordance with the inclination angle.
When the inclination angle α is 30° or less, adjust the feed rate to 70 % or lower as a guideline.
When the inclination angle α is greater than 30° , adjust the feed rate to 50 % or lower as a guideline.
3. This product is a tool intended for hole drilling. It cannot be used for cross-feed or helical machining.




MINI-MFE/MFE

Material	Properties	DC	L/D	n	$\alpha = 0^\circ$ fr
M Stainless steel	≤200HB	0.75	≤2	10600	0.007 (0.003 – 0.011)
		1.0	≤2	7900	0.007 (0.003 – 0.011)
		1.5	≤2	5300	0.010 (0.005 – 0.015)
		2.0	≤2	4700	0.015 (0.010 – 0.020)
		2.5	≤2	3800	0.015 (0.010 – 0.020)
		3.0	≤2	3100	0.020 (0.010 – 0.030)
		4.0	≤2	2300	0.030 (0.020 – 0.040)
		5.0	≤2	1900	0.040 (0.030 – 0.050)
		6.0	≤2	1500	0.050 (0.040 – 0.060)
		8.0	≤2	1100	0.060 (0.050 – 0.080)
		10.0	≤2	950	0.080 (0.060 – 0.100)
		12.0	≤2	790	0.100 (0.080 – 0.120)
		16.0	≤2	590	0.120 (0.100 – 0.150)
		20.0	≤2	470	0.150 (0.120 – 0.200)
K Gray cast iron	≤350MPa	0.75	≤2	23300	0.030 (0.010 – 0.050)
		1.0	≤2	17500	0.030 (0.010 – 0.050)
		1.5	≤2	12200	0.035 (0.015 – 0.055)
		2.0	≤2	9500	0.040 (0.020 – 0.060)
		2.5	≤2	7900	0.050 (0.030 – 0.070)
		3.0	≤2	7900	0.060 (0.040 – 0.080)
		4.0	≤2	5900	0.080 (0.060 – 0.100)
		5.0	≤2	4700	0.100 (0.080 – 0.120)
		6.0	≤2	3900	0.120 (0.100 – 0.140)
		8.0	≤2	2900	0.140 (0.120 – 0.160)
		10.0	≤2	2300	0.160 (0.140 – 0.180)
		12.0	≤2	1900	0.180 (0.160 – 0.200)
		16.0	≤2	1400	0.200 (0.180 – 0.240)
		20.0	≤2	1100	0.240 (0.200 – 0.280)
K Ductile cast iron	≤450MPa	0.75	≤2	16900	0.010 (0.005 – 0.015)
		1.0	≤2	12700	0.010 (0.005 – 0.015)
		1.5	≤2	10000	0.020 (0.010 – 0.030)
		2.0	≤2	8700	0.030 (0.015 – 0.045)
		2.5	≤2	7300	0.045 (0.025 – 0.065)
		3.0	≤2	6800	0.050 (0.040 – 0.060)
		4.0	≤2	5500	0.060 (0.050 – 0.080)
		5.0	≤2	4400	0.080 (0.060 – 0.100)
		6.0	≤2	3700	0.100 (0.080 – 0.120)
		8.0	≤2	2700	0.120 (0.100 – 0.150)
		10.0	≤2	2200	0.150 (0.120 – 0.180)
		12.0	≤2	1800	0.180 (0.150 – 0.200)
		16.0	≤2	1300	0.200 (0.180 – 0.250)
		20.0	≤2	1100	0.250 (0.200 – 0.300)
N Aluminium alloys	Si<5 %	0.75	≤2	42400	0.020 (0.010 – 0.030)
		1.0	≤2	31800	0.020 (0.010 – 0.030)
		1.5	≤2	21200	0.020 (0.010 – 0.030)
		2.0	≤2	17500	0.050 (0.030 – 0.070)
		2.5	≤2	14000	0.060 (0.040 – 0.090)
		3.0	≤2	11600	0.060 (0.040 – 0.090)
		4.0	≤2	8700	0.080 (0.060 – 0.100)
		5.0	≤2	7000	0.100 (0.080 – 0.130)
		6.0	≤2	5800	0.130 (0.100 – 0.160)
		8.0	≤2	4300	0.160 (0.130 – 0.200)
		10.0	≤2	3500	0.200 (0.160 – 0.240)
		12.0	≤2	2900	0.240 (0.200 – 0.280)
		16.0	≤2	2100	0.280 (0.240 – 0.320)
		20.0	≤2	1700	0.320 (0.280 – 0.360)

2/2



1. The recommended hole depth is DC x 2. This should be the depth from the uppermost surface of the workpiece when machining on an angled surface. (Refer to diagram)
2. The above cutting table assumes drilling on a flat surface.
For hole drilling on an angled surface, adjust the feed rate in accordance with the inclination angle.
When the inclination angle α is 30° or less, adjust the feed rate to 70 % or lower as a guideline.
When the inclination angle α is greater than 30° , adjust the feed rate to 50 % or lower as a guideline.
3. This product is a tool intended for hole drilling. It cannot be used for cross-feed or helical machining.





DFAS

APPLICATION EXAMPLE

Material	DIN 1.1213 / Cf 53
Tool/Drill	DFAS0800X03S080
Component	Machine parts
Vc (m/min)	100
fr (mm/rev.)	0.12
L/D (mm)	4.5
Cutting mode	Wet cutting
Coolant	Internal coolant (Water-soluble)
Machine	MC
Results	Cutting noise was reduced and the number of holes drilled was increased by 700 % when compared to a conventional product. The quality of the machined surface finish was also improved.



Material	DIN 1.0038 / St 37-2
Tool/Drill	DFAS1100X03S110
Component	Machine parts
Vc (m/min)	104
fr (mm/rev.)	0.12
L/D (mm)	27
Cutting mode	Wet cutting
Coolant	Internal coolant (Water-soluble)
Machine	MC
Results	Cutting noise was reduced and the number of holes drilled was increased by 300 % when compared to a conventional product. The quality of the machined surface finish was also improved.




■ DFAS ■ Conventional

The above examples are actual applications, therefore can differ from the recommended conditions.

APPLICATION EXAMPLE

Material	DIN GG-25
Tool/Drill	DFAS0830X03S090
Component	Machine Parts
Vc (m/min)	30
fr (mm/rev.)	0.05
Hole depth (mm)	1.5
Cutting mode	Wet Cutting internal Coolant (Water-soluble) Blind hole with 10° angled surface
Machine	Horizontal MC



Results

After drilling the same number of holes (1230) as the conventional product, the wear was minimal thereby allowing machining to continue.

AFTER DRILLING 1230 HOLES



Flank wear amount 0.10 mm
or less



Wear condition

MINI-MFE / MFE


CUTTING PERFORMANCE

COMPARISON OF EXIT BURRS GENERATED WHEN DRILLING STAINLESS STEEL

The unique cutting edge shape suppresses the formation of exit burrs.

INCLINATION ANGLE

Material	DIN X5CrNi189
Tool/Drill	MFE0200X02S040
Vc (m/min)	30
fr (mm/rev.)	0.01
Cutting mode	Wet cutting
Coolant	External coolant (Water-soluble)
Machine	Vertical MC (BT40)



INCLINATION ANGLE 0° / HOLE DEPTH = 4 MM



MFE




Conventional A




Conventional B

INCLINATION ANGLE 15° / HOLE DEPTH = 5 MM



MFE



Conventional A



Conventional B

INCLINATION ANGLE 30° / HOLE DEPTH = 7 MM



MFE



Conventional A



Conventional B

MINI-MFE/MFE

COMPARISON OF FRACTURE RESISTANCE WHEN MACHINING DIN X5CRNI1810


Achieved double tool life compared to conventional products because of the outstanding fracture resistance properties.

Material	DIN X5CrNi1810
Tool/Drill	MFE0600X02S060
Vc (m/min)	35
fr (mm/rev.)	0.025
Hole Depth	12 mm (l = DCx2)
Cutting mode	Wet cutting
Coolant	External coolant (Water-insoluble)
Machine	Vertical MC (BT50)


AFTER 50 HOLES MACHINING



MFE





MFE



Conventional



Conventional




MINI-MFE


Material	DIN X12CrNiS188
Tool/Drill	MFE0180X02S030
Component	Bolt
Vc (m/min)	22
fr (mm/rev.)	0.015
Cutting mode	Wet cutting
Coolant	External coolant
Machine	Small automatic lathe

Results

MFE – No accuracy errors even when used for continuous hole drilling on a small automatic lathe and gave at least double tool life.



LARGE BURR











MFE



Conventional

OPERATIONAL GUIDANCE

Drill holding	Drill length	Drill installation	Installation tolerance
 <p>Adjusting screw</p> <p>Thrust bearing type collet chuck holds the drill securely.</p>	 <p>$A > DC \times 1.5$</p>	 <p>NG</p> <p>Do not clamp on the flutes.</p>	 <p>Run-out < 0.03mm</p>
Thin workpiece	Burring and workpiece chipping	Coolant method (MFE)	Inclined face drilling
 <p>NG If bending occurs</p> <p>OK Support the workpiece</p>	 <p>Lower the feed rate by 50 % at the end of through cutting. Add a chamfer.</p>	 <p>Two coolant positions, at the end and at the centre are ideal.</p>	 <p>DC x 1</p> <p>When machining a deep hole into an inclined surface, use MFE drill (L/D=2) as a drill for a guide hole. Set the drill depth at approx. DC x 1 to obtain an accurate guide hole.</p>

EUROPEAN SALES COMPANIES

GERMANY

MMC HARTMETALL GMBH
Comeniusstr. 2 . 40670 Meerbusch
Phone +49 2159 91890 . Fax +49 2159 918966
Email admin@mmchg.de

UK Office

MMC HARDMETAL UK LTD
1 Centurion Court, Centurion Way
Tamworth, B77 5PN
Phone +44 1827 312312
Email enquiries@mitsubishicarbide.co.uk

UK Deliveries / Returns

Unit 4 B5K Business Park, Quartz Close
Tamworth, B77 4GR

SPAIN

MITSUBISHI MATERIALS ESPAÑA, S.A.
Calle Emperador 2 . 46136 Museros/Valencia
Phone +34 96 1441711
Email comercial@mmevalencia.es

FRANCE

MMC METAL FRANCE S.A.R.L.
6, Rue Jacques Monod . 91400 Orsay
Phone +33 1 69 35 53 53 . Fax +33 1 69 35 53 50
Email mmfsales@mmc-metal-france.fr

POLAND

MMC HARDMETAL POLAND SP. Z O.O
Al. Armii Krajowej 61 . 50-541 Wrocław
Phone +48 71335 1620 . Fax +48 71335 1621
Email sales@mitsubishicarbide.com.pl

ITALY

MMC ITALIA S.R.L.
Viale Certosa 144 . 20156 Milano
Phone +39 0293 77031 . Fax +39 0293 589093
Email info@mmc-italia.it

TURKEY

MMC HARTMETALL GMBH ALMANYA - İZMİR MERKEZ ŞUBESİ
Adalet Mahallesi Anadolu Caddesi No: 41-1 . 15001 35530 Bayraklı / İzmir
Phone +90 232 5015000 . Fax +90 232 5015007
Email info@mmchg.com.tr

www.mmc-carbide.com

DISTRIBUTED BY:

□

□

└

└

B233E 

Published by: MMC Hartmetall GmbH – A Sales Company of  MITSUBISHI MATERIALS | 2025.04